

ARUBA | ARUBA DOUBLE



ARUBA

Material	steel pipes \varnothing 28 mm / steel pipes \varnothing 22 mm
Connection thread	4 x G1/2"
Testing overpressure	1,3 MPa
Max. operating overpressure	1,0 MPa
Max. operating temperature	110 °C
Number of pipes	8, 13 17

ARUBA DOUBLE

Material	steel pipes \varnothing 28 mm / steel pipes \varnothing 22 mm
Connection thread	4 x G1/2"
Testing overpressure	1,3 MPa
Max. operating overpressure	1,0 MPa
Max. operating temperature	110 °C
Number of pipes	16, 26, 34




ARUBA

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input		Connection span [mm]
					75/65/20°C	70/55/20°C	55/45/20°C	paint [W]	chrome [W]	
1800/300	49	10,0	5,1	1,291	530	430	274	-	-	mc 50
1800/480	49	16,5	8,3	1,291	855	693	442	-	-	mc 50
1800/600	49	21,0	10,9	1,291	1064	862	550	-	-	mc 50

ARUBA DOUBLE

Type H/L [mm]	Depth B1 [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input		Connection span [mm]
					75/65/20°C	70/55/20°C	55/45/20°C	paint [W]	chrome [W]	
1800/300	70	19,5	10,0	1,307	834	674	433	-	-	mc 50
1800/480	70	31,5	16,3	1,307	1334	1079	693	-	-	mc 50
1800/600	70	40,5	21,2	1,307	1667	1348	866	-	-	mc 50

Thermal power measuring follows in accordance with EN 442.
Accessories (page 64, 65 and 66) is not part of the radiator.



Connection options

