

# SWING, SWINGO



## SWING, SWINGO

Material SWING	steel profiles 40 × 40 mm / steel profiles 25 × 25 mm
Material SWINGO	steel profiles 40 × 40 mm / steel pipes Ø 26 mm
Connection thread	2 × G1/2"
Testing overpressure	0,65 MPa
Max. operating overpressure	0,5 MPa
Max. operating temperature	110 °C
Number of profiles (pipes)	22, 30



SWING 1610 × 600

SWINGO 1610 × 610

## SWING

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input paint [W]	Recommended power input chrome [W]	Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C			
1210/600	54	25,1	7,7	1,20	690	568	374	700	-	50
1610/600	54	34,0	10,4	1,20	933	768	505	900	-	50

## SWINGO

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input paint [W]	Recommended power input chrome [W]	Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C			
1210/610	54	23,5	6,9	1,25	675	551	356	700	-	50
1610/610	54	31,9	9,3	1,25	914	746	483	900	-	50

Thermal power measuring follows in accordance with EN 442.

The cover of radiator in other colour is available per order.

Accessories (page 64, 65 and 66 is not part of the radiator.

