

Material:	steel profiles 70 x 50 mm / steel profiles 70 x 11 mm / stell pipes Ø 28 mm
Max. operating temperature:	90 °C
Numbers of profiles:	4, 6, 8
Option 1 - with heating rod Z	
Working voltage	230 V/50 Hz
Maximum el. power	1350 W
Connection thread	G 1/2" outer
Protection / Class	IP 44 / class I
Connection cord	coiled el. cord length 120 cm / distended about 350 cm / with plug
Option 2 - with controller Mini	
Working voltage	230 V/50 Hz
Maximum el. power	1200 W
Connection thread	G 1/2" outer (on the heating rod)
Protection / Class	IP X4 / class I
Connection cord	direct el. cord length 120 cm with plug
Colour of connection cord	white / grey
Colour of controller	white / chrome
Option 3 - with controller Forte	
Working voltage	230 V/50 Hz
Maximum el. power	1200 W
Connection thread	G 1/2" outer (on the heating rod)
Protection / Class	IP X4 / class I
Connection cord	direct el. cord length 120 cm with plug
Colour of connection cord	white / grey
Colour of controller	white / chrome
Option 4 - with controller KTX 3	
Working voltage	230 V/50 Hz
Maximum el. power	1000 W
Connection thread	G 1/2" outer (on the heating rod)
Protection / Class	IP X5 / class I
Connection cord	direct el. cord length 150 cm with plug
Colour of connection cord	white / grey
Colour of controller	white / chrome
Display	LCD display



VITAL 1800x450



Type H/L [mm]	Depth [mm]	Weight [kg]	Heating rod Z [W]	Recommended power input		
				Controller Mini [W]	Controller Forte [W]	Controller KTX 3 [W]
1800/298	50	25,4	800	800	800	800
1800/450	50	38,0	1000	1000	1000	1000
1800/602	50	50,7	1200	1200	1200	1000

The weight of radiator is listed with antifreeze fluid.

